

Geared Head Heavy Duty Lathe with Norton Gearbox

- Geared Head Heavy Duty Lathe with Norton Gearbox
- Flame Hardened Bed
- Model GH-12 lathe with Cabinet Stand
- All other models with Planner Type Bed

Model:	GH-12
Centre height (mm):	375
Admit between centres (mm):	2000
Width of bed (mm):	450
Spindle bore (mm):	104
Swing over bed (mm):	750
Swing in gap (mm):	1050
Width of gap in front of faceplate (mm):	575
Swing over cross slide (mm):	475
Thread range (mm):	0.5 - 7.5
Thread range TPI (Inches):	4 - 60
Lead screw (TPI):	4
Number of Speed / Range (no / rpm):	8 / 15 - 400
Power requirement (HP):	5
Net / Gross weight (kg)	3100 / 3400
Overall Dimensions (m):	4.2 x 1.2 x 1.35
Approximate Shipping Volume (m ³):	6.8



Model: GH-12 with Cabinet type stand



Model: GH-16 with Planner type stand

Model:	GH-14	GH-16	GH-20
Centre height (mm):	375	375	375
Admit between centres (mm):	2500	3000	4000
Width of bed (mm):	450	450	450
Spindle bore (mm):	104	104	104
Swing over bed (mm):	750	750	750
Swing in gap (mm):	1050	1050	1050
Width of gap in front of faceplate (mm):	575	575	575
Swing over cross slide (mm):	475	475	475
Thread range (mm):	0.5 - 7.5	0.5 - 7.5	0.5 - 7.5
Thread range TPI (Inches):	4 - 60	4 - 60	4 - 60
Lead screw (TPI):	4	4	4
Number of Speed / Range (no / rpm):	8 / 15 - 400	8 / 15 - 400	8 / 15 - 400
Power requirement (HP):	5	5	5
Net / Gross weight (kg)	3400 / 3800	3800 / 4200	4800 / 5300
Overall Dimensions (m)	4.8 x 1.2 x 1.35	5.4 x 1.2 x 1.35	6.0 x 1.2 x 1.35
Approximate Shipping Volume (m ³)	7.8	8.8	9.8

Standard Accessories: Face plate, Drive plate, Steady rest, Follow rest, Thread dial indicator, 4-way tool post, one M.T. centre, 3 and 4 Jaw chuck, suitable motor with control panel, coolant pump and machine lamp.

Optional Accessories: Taper Turning Attachment (Can be supplied only if ordered with the Lathe)